

Uninstall Zend Server for IBM i - Zend Server 6 - 8.5.x, Zend Server 9.1.x, Zend Server 2018.x and Zend Server 2019.x

Issue

This article tells how to uninstall Zend Server for IBM i, version 6 - 8.5.x, Zend Server 9.1.x, Zend Server 2018.x and Zend Server 2019.x.

For **Zend Server version 5**, please go here: [Uninstall Zend Server 5 for IBM i](#)

For **Zend Server 2020.x** and higher, please go to the online installation instructions found here: [Uninstall Zend Server for IBM i - Version 2020.x and higher](#)

Environment

Zend Server for IBM i Zend Server 6 - 8.5.x, Zend Server 9.1.x, Zend Server 2018.x and Zend Server 2019.x, running on any supported version of IBM i.

Zend Server version 9.1.x, Zend Server 2018.x, Zend Server 2019.x.

These are the steps to uninstall Zend Server 9.1.x, Zend Server 2018.x, Zend Server 2019.x

From the 5250 command line, signed on as QSECOFR or with a *SECOFR class profile:

```
WRKOBJLCK OBJ(ZENDPHP7) OBJTYPE(*LIB)
```

End any jobs displayed. Then:

```
GO LICPGM
```

Use option "12. Delete licensed programs"

Find product 7PHPZND, Zend Server for IBM i, on the list. Use option 4 to Delete it.

Note:

If you are uninstalling for a clean install, and plan to reinstall the same version of the software, look at the description on this screen to determine the currently installed version of Zend Server and PHP, before you delete the licensed program.

The delete process will back up certain files to preserve configuration and application files. The backup directory names will be in the format zendphp7TIMESTAMP, where TIMESTAMP is a numeric timestamp representing the date and time the backup was made. The backup directories will be /usr/local/zendphp7TIMESTAMP and /www/zendphp7TIMESTAMP. These directories can be deleted manually once the backup is no longer needed. If you plan to reinstall Zend Server, keep these directories. You can use the contents to restore your settings.

Zend Server versions 6 - 8.5.x:

These are the steps to uninstall Zend Server 6, 7, 8, or 8.5 for IBM i:

From the 5250 command line, signed on as QSECOFR or with a *SECOFR class profile:

```
WRKOBJLCK OBJ(ZENDSVR6) OBJTYPE(*LIB)
```

End any jobs displayed. Then:

```
GO LICPGM
```

Use option "12. Delete licensed programs"

Find product 6ZSVRPI, Zend Server for IBM i, on the list. Use option 4 to Delete it.

Note:

If you are uninstalling for a clean install, and plan to reinstall the same version of the software, look at the description on this screen to determine the currently installed version of Zend Server and PHP, before you delete the licensed program.

The delete process will back up certain files to preserve configuration and application files. The backup directory names will be in the format `zendsvr6TIMESTAMP`, where `TIMESTAMP` is a numeric timestamp representing the date and time the backup was made. The backup directories will be `/usr/local/zendsvr6TIMESTAMP` and `/www/zendsvr6TIMESTAMP`. These directories can be deleted manually once the backup is no longer needed. If you plan to reinstall Zend Server, keep these directories. You can use the contents to restore your settings.