Delete Licensed Program - (DLTLICPGM) Zend Platform for i5/OS (ZENDCORE)

Applies To:

[Zend Core 2..x] [IBM System i]

Overview

The Delete Licensed Program (DLTLICPGM) command is used with the i5/OS to delete all the objects that make up the licensed program. When a change is made to any of the LP objects, an object is added to a library or a directory that is stamped as a part of the LP the delete license program command may fail at times.

Instructions

Perform a clean uninstall of Zend Platform for i5/OS

- 1. The Delete Licensed Program (DLTLICPGM) command, from an i5 command line:
 - DLTLICPGM remove the product 1ZCORE5 OPTION(1) from the system.
 - WRKOBJLCK OBJ(ZENDPLAT) OBJTYPE(*LIB)
 - DLTLICPGM LICPGM(1ZCORE5) OPTION(1)

Note:

Make sure the library ZENDPLAT is not locked by any other job including yours, except for the ZEND subsystem jobs. (i5_COMD, ZC_STR_PRN, ZENDCOREAP, ZSTRCLCNTR, ZSTRJAVAMW ZSTRMYSQL)

Complete these steps for a failed uninstall

- 1. From an i5 command line:
 - ENDSBS ZEND end the subsystem if active
 - WRKLIB ZENDPLAT select option 12 to work with library
 - WRKOBJPDM LIB(ZENDPLAT) OBJ(ZPLATI5) identify the object:
 - ZPLATI5 * PRDLOD Zend Platform product load
 - Select option 4= delete remove the product load.
 - DLTLIB ZENDPLAT
 - Remove or Rename the Zend platform directories /usr/local/Zend/Platform & /usr/local/Zend/MySQL
- 2. Rename the directories:
 - WRKLNK '/usr/local/zend' and select option 7 rename the directory /Platform
 - WRKLNK '/usr/local/zend' and select option 7 rename the directory /MySQL
- 3. Remove the directories:
 - CALL QP2TERM to start the PASE terminal shell
- 4. From the terminal shell enter the commands:
 - rm -rf /usr/local/zend/Platform
 - rm -rf /usr/local/zend/MySQL
- 5. You can use the following i5 commands as well to remove the product this step is the same as before to remove the directories:
 - QSYS/CD DIR(/)
 - QSYS/CALL PGM(QP2SHELL) PARM('/QOpenSys/usr/bin/ksh' 'rm -rf /usr/local/zend/Platform')
 - QSYS/CALL PGM(QP2SHELL) PARM('/QOpenSys/usr/bin/ksh' 'rm -rf /usr/local/zend/MySQL')

For more information on i5/OS commands see IBM Information Center (links below)

Excerpt: The Delete Licensed Program (DLTLICPGM) command is used with the i5/OS to delete all the objects that make up the licensed program. When a change is made to any of the LP objects, an object is added to a library or a directory that is stamped as a part of the LP the delete license program command may fail at times.

External Links:

IBM Information Center

Alternative Description:

Delete Licensed Program - (DLTLICPGM) Zend Platform for i5/OS